

IN THE CLAIMS:

1. (currently amended) A washing machine comprising:

a tub;

a resistance network comprising a sensor, a resistor, and a voltage source, said sensor
positioned and configured to sense a conductivity of a fluid in said tub; and

a controller operatively coupled to said sensor and configured to control an amount of
the fluid in said tub during a rinse cycle based on the conductivity of the fluid measured at an
end of a wash cycle.
2. (currently amended) A washing machine according to Claim 1, wherein said
sensor is positioned within said tub.
3. (currently amended) A washing machine according to Claim 1, wherein said
sensor is positioned outside said tub.
4. (previously presented) A washing machine according to Claim 1, wherein said
sensor is configured to sense an initial conductivity of the fluid during the wash cycle without
detergent.
5. (previously presented) A washing machine according to Claim 4, wherein said
sensor is further configured to sense a final conductivity of the fluid after the wash cycle with
detergent.
6. (previously presented) A washing machine according to Claim 5, wherein said
controller is configured to determine a desirable achievable rinse level by calculating the
difference between the initial conductivity and the final conductivity.
7. (previously presented) A washing machine according to Claim 1, wherein said
controller is configured to measure the conductivity of the fluid sensed by said sensor during
the wash cycle without detergent and during the wash cycle with detergent.

8. (original) A washing machine according to Claim 7, wherein said controller is configured to measure the conductivity of the fluid sensed by said sensor over at least a 3 second period.

9. (previously presented) A washing machine according to Claim 7, wherein said controller is configured to calculate an overall change of conductivity of the fluid.

10. (previously presented) A washing machine according to Claim 9, wherein said controller is configured to compare the overall change of conductivity with a desirable achievable rinse level.

11.-23. (canceled)